

ANNULAR TUBE OVEN. MODEL CTA.



The Saturno CTA oven exactly reproduces the type of bake provided by a traditional rotary oven. The annular tube system makes this the perfect oven to bake any kind of artisan bread, or any other speciality of bread or pastries. This oven has the following characteristics:

- Annular Tube Oven bakes via refractory floor base, or on trays via radiant heat.
- The strength of the Saturno CTA is the high quality crust and bread base. Better dough integrity and stability without any loss of volume after baking.
- Perfect steam control in each baking chamber with twin steam system.
- Built with high quality refractory material, guaranteed long-lasting and energy-saving for a uniform bake.
- The burner is located in the rear part of the oven and works with any fuel, be that oil, gas or biomass
- The hood has been designed to avoid steam condensation and fitted with a suction system for when in use.
- Because of its solid build, it requires no maintenance, as breakdowns are virtually non-existent.
- Depending on the products to be baked, it can be built with 5 or 7 decks of two different width openings, of 1.000 or 1.200. (measurements in mm).
- Different sizes of floors, 1.300, 1.600 and 2.000. (measurements in mm).

NOTE: As we are the manufacturers we can adapt to your requirements.

EXTERNAL DIMENSIONS.

▪ OVEN MODELS 5 DECKS:

MODEL	COOKING SURFACE	BAKING AREA			EXTERIOR		
		WIDTH	DEPTH	HEIGHT	WIDTH	DEPTH	HEIGHT
CTA -120 5P -1.0	6,5 mts2	1.000	1.300	200	1.800	2.410	2.400
CTA 180 5P - 1.0	8 mts2	1.000	1.600	200	1.800	2.700	2.400
CTA-240 5P- 1.0	10 mts2	1.000	2.000	200	1.800	3.135	2.400
CTA-120 5P-1.2	7,8 mts2	1.200	1.300	200	2.000	2.410	2.400
CTA-180- 5P-1.2	9 mts2	1.200	1.600	200	2.000	2.700	2.400
CTA-240- 5P-1.2	12 mts2	1.200	2.000	200	2.000	3.135	2.400

▪ OVEN MODELS 7 DECKS:

MODEL	COOKING SURFACE	BAKING AREA			EXTERIOR		
		WIDTH	DEPTH	HEIGHT	WIDTH	DEPTH	HEIGHT
CTA-120- 7P -1.0	9,10 mts2	1.000	1.300	160	1.800	2.410	2.400
CTA -180- 7P - 1.0	11,20 mts2	1.000	1.600	160	1.800	2.700	2.400
CTA-240- 7P 1.0	14 mts2	1.000	2.000	160	1.800	3.135	2.400
CTA-120- 7P-1.2	10,92 mts2	1.200	1.300	160	2.000	2.410	2.400
CTA-180- 7P-1.2	13,44 mts2	1.200	1.600	160	2.000	2.700	2.400
CTA-240- 7P-1.2	16,80 mts2	1.200	2.000	160	2.000	3.135	2.400

